D.

AS-BUILT DRAWINGS

Appendix D Operations and Maintenance Manual

(PROJECT NAME)

(SAMPLE) TABLE OF CONTENTS

PARA.	TITLE	PAGE NO.
	SECTION I - INTRODUCTION	
I-1. I-2. I-3. I-4. I-5.	PURPOSE OF THIS MANUAL AUTHORIZATION LOCATION DESCRIPTION OF PROJECT PROTECTION PROVIDED CONSTRUCTION HISTORY LOCAL COOPERATION AGREEMENT	
I-7.		
	SECTION II - OPERATION AND MAINTENANCE	
II-1. II-2. II-3. II-4. II-5. II-6. II-7.	GENERAL MANAGEMENT DUTIES PERIODIC INSPECTIONS REPORTS IMPROVEMENTS OR ALTERATIONS PROJECT FEATURES (Description, Operation, Maintenance)	
	SECTION III - PERIODIC NOURISHMENT	
III-1. III-2. III-3. III-4. III-5. III-6. III-7	SCOPE MONITORING (Surveys, Aerial Photography, Sediment Samples, Waves, etc.) NOURISHMENT ROUTINE MONITORING ANALYSIS POST-STORM ANALYSIS POST-STORM MAINTENANCE POST-STORM NOURISHMENT	
	SECTION IV - RESPONSIBILITIES	
IV-1. IV-2. IV-3.	U.S. ARMY CORPS OF ENGINEERS LOCAL SPONSOR FINANCIAL	
	APPENDICES	
A. B. C.	ENGINEER REGULATION NO. 1110-2-2902 LOCAL COOPERATION AGREEMENT INSPECTION REPORT FORMS	

EM 1110-2-3301 31 May 95

- D-1. The inspection forms furnished in this appendix are samples from which the user should design forms that reflect specific project features. Instructions should be tailored to the Superintendent so that he knows how many beach and dune forms and how many structural forms he needs to complete during an inspection.
- D-2. Assuming that the protection device is primarily the beach, berm, and dune, a form has been developed for that portion of the project. That form may need only minimal revision to suit the user's purposes. For example, the project name will need to be inserted. The user may also need to instruct the Superintendent at which stations he should inspect the beach. This may be uniformly along the shore, e.g., every 1,000 to 5,000 ft or at specific locations, e.g., dune crossovers, ramps, or parking lots.
- D-3. The project may include erosion-control structures to protect the beach and dune. A terminal groin, system of groins, system of offshore breakwaters, or other structure may be included in the project. The structure inspection form needs to be modified to depict each of these structures. If the structure is not made of stone, other revisions will be needed to help the superintendent inspect the project. He will need to be furnished with forms for each type of feature so that he can fill out one form for each structure.

	INSPECTION FORM BEACH AND DUNE (PROJECT NAME)		Station+_	
DATE OF INSPECTION: YEAR MONTH DAY	_		COMMENTS	
TYPE OF INSPECTION: REGULAR POST-STORM				
EROSION?	YES	NO		
STA+ to STA+_ Estimated VolumeCY				
ACCRETION?	YES	NO		
STA+ to STA+ Estimated Volume CY				
BEACH SCARP?	YES	NO		
STA+ to STA+_ Estimated Height FT				
OVERTOPPING OF BERM OR DUNE DURING HIGH WATER?	YES	NO		
STA+ to STA+_ Estimated Depth FT				
ENCROACHMENT? Structural	YES	NO		
Pedestrian Vehicular	YES YES YES	NO		
If YES, Describe remedy used!>				
SAFETY? GOOD FAIR POOR				
Parking Rules Life Guards during Swimming Season	YES YES	NO		
PREPARED BY: PREPARER		CERTIFIED B		
SIGNATURE			SIGNATURE	

INSPECTION FORM BEACH AND DUNE (PROJECT NAME)	Date:	SHEET 2 OF 2 YEAR MONTH DAY
CONDITION OF VEGETATIVE COVER	СОММЕ	ENTS
GOOD FAIR POOR Plants per square meter		
Destroyed or Dying YES NO STA+_ to STA+		
Excessive weeds YES NO STA+ to STA+		
CONDITION OF SAND FENCING GOOD FAIR POOR		
BEACH ACCESS GOOD FAIR POOR		
OTHER DAMAGE YES NO STA + to STA + YES NO Write a detailed comment>		
MAINTENANCE SINCE THE LAST INSPECTION YES NO Write a detailed comment>		
SURVEYS CONDUCTED SINCE THE LAST INSPECTION NOTE: A minimum of one survey must be made annually. A comparison of the original survey of this range and the last three surveys should accompany this report of inspection.		
Last survey date:		
BEACH CLEANLINESS? GOOD FAIR POOR		
Trash barrels YES NO		
CONDITION OF PARKING LOT GOOD FAIR POOR		

STR	RUCTURA	ON FORM AL FEATURE CT NAME)	Station+_
DATE OF INSPECTION: YEAR MONTH DAY			COMMENTS
TYPE OF INSPECTION: REGULAR POST-STORM			
DAMAGE TO TRUNK LEFT SIDE RIGHT SIDE Groin STA + to STA + Length FT Width FT Depth FT	_ YES	NO	
SLUMPING/SLUFFING STONE DETERIORATION EXPOSED UNDERLAYER	YES	NO NO NO NO NO NO NO NO NO	
DAMAGE TO CREST	_ YES	NO	
STONE DETERIORATION EXPOSED UNDERLAYER	YES YES YES YES YES YES YES	NO NO NO NO NO	
DAMAGE TO HEAD	_ YES	NO	
SLUMPING/SLUFFING STONE DETERIORATION	YES YES YES YES YES YES YES YES YES	NO NO NO NO NO NO NO NO	
PREPARED BY: PREPARER		CERTIFIED BY	
SIGNATURE	_		SIGNATURE

INSPECTION FOR STRUCTURAL FEAT (PROJECT NAME	URE		Date:	SHEET 2 OF 2 YEAR MONTH DAY
GENERAL STONE DAMAGE	YES	NO	СОММІ	ENTS
PITTING SPALLING ROUNDING CRACKING BREAKING OTHER (Comment)	YES YES YES YES YES YES YES	NO NO NO NO NO NO NO NO		
GENERAL CONDITION GOOD FAIR POOR				
GOOD INTERLOCKING STONES STABLE FOR NORMAL WAVES?	YES	NO NO		
BEACH AND NEARSHORE BOTTOM CO	ONDITION			
SAND WASHING THROUGH GROIN? LengthFT WidthFT DepthFT	YES	NO		
SCOUR AT HEAD? LengthFT WidthFT DepthFT				
SCOUR ALONG TRUNK? Length FT Width FT Depth FT				
MAINTENANCE SINCE THE LAST INSPECTION Write a detailed comment>	YES	NO		
SURVEYS CONDUCTED SINCE THE LAST INSPECTION NOTE: A minimum of one survey must be comparison of the original survey of this rasurveys should accompany this report of in	ange and the			
Last survey	date:	MONTH DAY		